



COMPTON BUILDINGS TEXTURED FINISH – DETAILED INFORMATION

Compton's new joint-free textured finish, features a coating supplied by a leading supplier of construction coatings. This information sheet provides an abbreviated version of useful information issued by the supplier:

Outstanding Durability

The choice of 4 textured finishes provide extremely tough, flexible and long lasting decorative protection for virtually all common building substrates. Because the texture in the range is created using naturally occurring crushed marble aggregates, the life expectancy of the finish is considerably longer than other products using friable perlite fillers. These solvent borne textures have a long life expectancy of up to 20 years in adverse conditions.

Fast Drying and Easy to Apply

Textures show high UV resistance ensuring lasting colour retention. The material is supplied ready for Compton use and is applied using a trowel and roller.

All Year Application

May be applied in extreme weather conditions making them the perfect choice for builders and developers during the winter months, when low temperatures and imminent rainfall prohibit the use of water borne systems.

Over-painting

If required, the textured finish can be over-painted using a good quality masonry paint.

Product Information

DESCRIPTION - Exceptionally durable, solvent-based, ready-to-use textured coating, with crushed marble aggregates.

USAGE/PURPOSE - For the exterior decoration and long life protection of virtually all common building substrates.

CHARACTERISTICS - Solvent-borne: all year round use. Excellent adhesion to all sound substrates. Ready to use. Weatherproofing, yet moisture vapour permeable. Self priming. Alkali resistant.

PERFORMANCE - Exceptionally durable. Will provide at least **20 years** protection (*when correctly applied on sound substrates*). Tested to BS476: Parts 6 and 7 and satisfies Class 0 requirements. Rain resistant 20 minutes after application. Can be applied, and will dry, at temperatures below 0°C. Texture hides surface defects. Flexible film resists cracking. Fade resistant colours

FINISH - Matt, textured.

ENVIRONMENTAL CONSIDERATIONS - Contains no added lead.

Technical Specification

COMPOSITION - Tough, flexible acrylic resins in white spirit, with crushed marble aggregates, titanium dioxide, light-fast earth pigments.

NOTE: This product contains a fungicide/algaecide for the sole purpose of protecting the film.

Application

ACCESS - ACCESS OF AT LEAST 1 METRE (3 ½ft) IS REQUIRED TO ALL SIDES TO APPLY FINISH!

Trowel/roller: Typically 2.5 - 5 kg per m²

DRYING TIME - Dependent upon weather conditions and temperature. Average times are:

Working time: 30 minutes approx. *Touch dry:* 8 hours. *Hard dry:* 24 to 48 hours. *Full cure:* 1 week.

For more information contact Compton Buildings:

Tel 01295 770291

Fax 01295 770748

Web www.ComptonBuildings.co.uk

Email sales@compton-buildings.co.uk